

PX1

HYDROCARBON EXTRACTOR

PRECISION
EXTRACTION SOLUTIONS

By **AGRIFY**

3-5 LB
Per Hour Processing*



PX1

HYDROCARBON EXTRACTOR

The small footprint of the PX1 is perfect for proving your concept and scaling up. We've completed hundreds of successful installations and had proven results with this economical cannabis extractor and its fast recovery times.

The PX1 cannabis extractor comes packed with several convenient features, chief among them being pre-plumbed for chillers and heaters, and is rack mounted to make loading and unloading material columns a breeze.

This system is a great addition to labs looking to add a craft concentrate line to their product offering.

SYSTEM HIGHLIGHTS



PRECISE CONTROL
Over Primary Extraction



ECONOMICAL HYDROCARBON SOLUTION
For Cannabis Extraction



SMALL FOOTPRINT
Big Results



RACK-MOUNTED
Easy Load & Unload Material Columns



FIELD VERIFICATION INCLUDED

PX1

HYDROCARBON EXTRACTOR

Economical & Highly Effective

- Approximately 11L, 5 lb material capacity*
- 1/2" PTFE/SS feed hosing (UL-21 compliant)
- Stackable and variable filtering
- Vacuum jacket insulated solvent/dewax vessels
- Nitrogen/argon assist ready
- Patent-pending vessel temperature control systems
- Ultra efficient internal temperature coil mechanisms
- Pre-plumbed for chillers and heaters
- CD-BC12 recirculating heat bath (see cut sheet)
- FP50-HE recirculating chiller (see cut sheet)



Solvents:
Butane, Propane & Blended

Processing:
3-5 lb per Hour*

Batch Cycle Time:
30-45 Minutes*

Capacity:
Up to 40 lb, per 8-hr Shift*

Extracts:
Isolate, Sauce, Distillate, Vape Pens, Shatter, Wax/Sugar, Tincture and Edibles

Equipment Specifications

Dimensions (approx.)	51" L x 46" W x 93" H
Weight (approx.)	346 lb
Shipping Weight (approx.)	700 lb
MAWP	250 PSIG
Warranty**	One-Year

Compliance



- PSI Certified in All 50 States
- 100% ASME Stamped & Rated Vessels
- ASME Certified PRVs (Pressure Relief Valve)

- ASME Certified Clamps (6"+)
- Third-Party Engineer Report
- Pressure Test Report
- Build Report
- Serial Number

Chiller Pairing Recommendations



Julabo FP-50, Huber Equivalent, or better (Crude)

Julabo FP-89, Huber Equivalent, or better (Shatter, Wax, Live Resin, etc.)

OPTIONAL Chiller Upgrades Available to **FP89-HL**



Precision Extraction Solutions
855-420-0020 | info@precisionextraction.com
PrecisionExtraction.com

*Actual amount of material per run and recovery times on any Precision® extraction system varies depending on composition, cut and moisture of input material, humidity and environmental factors, processing temperatures and operator experience. **See Warranty Terms. Please refer to operational manual for important safety warnings and legal disclaimers.