DRY & DECARB OVENS



DRY

- · Powerful Lab Oven
- · Uniform Air Flow

DECARB

- · Save Time
- Increase Yields

Removing moisture and decarboxylation of plant material prior to processing is an effective way to decrease run times and increase overall yield.

Typical decarboxylation practices are ≈240°F for ≈1 hour and 15 minutes.



Automatic Operation with Easy Timer



Overtemp Protection

Monitor Moisture During Process

INCLUDES

Easy Loading Ground Organic Material with Temp Rated, Large Capacity Mesh Bags. Max airflow efficiency

Certified at No Extra Cost NRTL Certified

CSA & CE Approved

Food Grade Stainless interior

1-Year Warranty









503.847.9047 info@cascadesciences.com cascadesciences.com ©2017 Cascade Sciences Inc.

WANT TO LEARN MORE?



DRY & DECARB OVENS



NRTL CERTIFICATION

CAN/CSA-C22.2 No. 61010-1:2012 + UPD No. 1:2015-07 + UPD No. 2:2016-04

CAN/CSA-C22.2 No. 61010-2-010:2015

UL 61010-1:2012/R:2016-04 UL 61010-2-010:2015 EN 61010-1:2010

EN 61010-2-010:2014





MODEL CDO-5
BENCHTOP



MODEL CDO-28 INDUSTRIAL

Access Port:	2.75" Diameter (Rear)	2.75" Diameter (Rear)
Exterior:	34.1"W x 28.1" D x 38.75"H	43" W x 34.3" D x 85.5" H
Interior:	21"W x 19.44"D x 20.75"H	31.5" W x 26" D x 60.5" H
CAPACITY	4.9 Cubic Ft	28 Cubic Ft

SHELVING 2 Each. Adjustable 6 Each. Adjustable 20.75"W x 19"D 31.1" W x 23.9"D

Maximum: 9 Shelves/4 Mesh Bags 16 Shelves/10 Mesh Bags Weight Capacity: 50 lbs 75 lbs

Mesh Bags: 2 Included - 15.5"D x 21"W 6 Included - 28.5"W X 22"D

TEMPERATURES

Range: Ambient +26° to 350°F Ambient +26° to 350°F

Without HumiditySensor: To 500F To 500F
Uniformity: 1.5F @ 240°F 3.6F @ 240°F

AIRFLOW

Across Shelf Space: 15.2 cubic ft per min 17.7 cubic ft per min

FACILITIES

Power: 120V / 1ph / 14A 230V-240V/1ph/26A (208V OK)
Cord Type: 110V-120V NEMA 5-15 9'5"L None. Must Be Hardwired

Air Intake (Adjustable): Side Vents Top 2.75" Dia
Air Exhaust (Adjustable): Top 2.75" Dia

Air Exhaust (Adjustable): Top 2.75" Dia Top 2.75" Dia Recommended Clearance: 12-24" all sides 12-24" all sides

WEIGHT 208 lbs 565 lbs Shipping: 258 lbs 694 lbs



WANT TO LEARN MORE?

503.847.9047 info@cascadesciences.com cascadesciences.com ©2017 Cascade Sciences Inc.